

Arcus LBo5-KRo1

Kraan open/dicht, een water aansluiting.
Tap open/close, one water affiliation.

UITRUSTING

Afmeting profiel:	150 mm x 50 mm
Materiaal:	RVS 304
Afwerking:	geborsteld RVS
Douchekop:	geïntegreerde kunststof douchekop 190 mm x 130 mm
Kraan:	enkele aansluiting open/dicht functie RVS 304
Omstel:	nvt
Handdouche:	nee
Voetdouche:	nee
Montage:	U-profiel in kolom (standaard) RVS 304
Grondbevestiging:	zie pagina 78 t/m 81
Aanbevolen waterdruk:	2-4 bar aan douchekolom
Aansluiting	naar waterleiding G 1/2
Optioneel:	bevestigings flens met afdekkap RVS 304 i.p.v. U-profiel
Kleur:	ook verkrijgbaar in zwart (RAL Volcanic en RAL 9005), zie accessoires

EQUIPMENT

Dimension of profile:	150 mm x 50 mm
Material:	Stainless steel/ Inox Aisi 304
Finish:	brushed stainless steel
Showerhead:	integrated showerhead 190 mm x 130 mm
Tap:	single jack open/close function stainless steel/Inox Aisi 304
Diverter:	does not apply
Hand shower:	no
Foot shower:	no
Mounting:	U-profile in column (standard) stainless steel/Inox Aisi 304
Ground Fixing:	see page 78 utai 81
Recommended waterpressure:	2-4 bar
Connection:	watersupply G 1/2
Optional:	mounting flange with cover stainless steel/Inox 304 instead of U-profile
Colour:	also available in black (RAL Volcanic and RAL 9005), see accessories

